

# Pulsed, Single-Frequency, 2-um Seed Source for Coherent LIDAR Applications, Phase I


Completed Technology Project (2010 - 2010)



## Project Introduction

The primary objective of the proposed Phase I effort is to develop and demonstrate a low-average power, pulsed, single-frequency, 2-um Ho-laser source for application as a front end in coherent LIDAR systems. Development of such pulsed seed sources is critical for the design of compact, rugged, reliable and efficient LIDAR transmitters based on all-amplifier architecture. Pulsed operation of the Ho-oscillator is achieved via passive Q-switching using robust Cr<sup>2+</sup>-doped saturable absorbers. Such seed oscillators allow generation of ns-width pulse trains at kHz repetition rates. Direct diode-pumping using the latest 1.9-um diode laser technology provides improved oscillator reliability and compactness. The choice of a 2-um Ho-laser material (as opposed to 1.5-um Er-lasers) enables efficient power/energy scaling of the pulsed seed oscillator output in high-gain Ho-amplifiers. This approach decreases the number of amplifying stages, simplifies the overall design and packaging, and improves the electrical efficiency of the complete laser system as compared to the current technology.

## Primary U.S. Work Locations and Key Partners



Pulsed, Single-Frequency, 2-um Seed Source for Coherent LIDAR Applications, Phase I

## Table of Contents

Project Introduction	1
Primary U.S. Work Locations and Key Partners	1
Project Transitions	2
Organizational Responsibility	2
Project Management	2
Technology Maturity (TRL)	3
Technology Areas	3
Target Destinations	3

## Pulsed, Single-Frequency, 2-um Seed Source for Coherent LIDAR Applications, Phase I

Completed Technology Project (2010 - 2010)



Organizations Performing Work	Role	Type	Location
Q-Peak, Inc.	Lead Organization	Industry	Bedford, Massachusetts
● Langley Research Center(LaRC)	Supporting Organization	NASA Center	Hampton, Virginia

Primary U.S. Work Locations	
Massachusetts	Virginia

## Project Transitions

**January 2010:** Project Start**July 2010:** Closed out**Closeout Documentation:**

- Final Summary Chart(<https://techport.nasa.gov/file/139989>)

## Organizational Responsibility

**Responsible Mission Directorate:**

Space Technology Mission Directorate (STMD)

**Lead Organization:**

Q-Peak, Inc.

**Responsible Program:**

Small Business Innovation Research/Small Business Tech Transfer

## Project Management

**Program Director:**

Jason L Kessler

**Program Manager:**

Carlos Torrez

**Principal Investigator:**

Alex Dergachev

**Co-Investigator:**

Alex Dergachev


# Pulsed, Single-Frequency, 2-um Seed Source for Coherent LIDAR Applications, Phase I

Completed Technology Project (2010 - 2010)



## Technology Maturity (TRL)

Start: **3**  
Current: **4**  
Estimated End: **4**



## Technology Areas

### Primary:

- TX08 Sensors and Instruments
  - └ TX08.1 Remote Sensing Instruments/Sensors
    - └ TX08.1.5 Lasers

## Target Destinations

The Sun, Earth, The Moon, Mars, Others Inside the Solar System, Outside the Solar System